# SHERPA 10ECO





### **TECHNICAL DATA SHERPA 100 ECO**

Motor

Type Pmac Capacity 1.5/2 kW/pk Revolutions per minute 1800 rpm Adjusted amount of revolutions 1800 rpm

Cooling Air cooled

**Drive system** Hydrostatic through 2 hydraulic wheel motors

0-3,5 (proportional) km/h **Speed** 

**Capacity data** 

Breakout force 497 kg Tractive force 250 kg

Hydraulic drive- and working system 14,4/150 l/bar

38 l Hydraulic tank capacity

**Tires** 

Standard 4.00x10 - Trac profile tires Wide 20x11.00-8 - Trac profile tires

**Brakes** 

Braking system Hydrostatic on 2 rear wheels/2 front wheels


through chain transmission


Steering Skid steering

**Electrical system** 

24 V Voltage **Battery capacity** 360 Ah

**Dimensions in mm** 





A Maximum height with bucket up	2545	J Bucket angle high	53°
B Height hinge point coupling plate	2050	K Wheelbase	657
C Maximum height with bucket low	1195	L Length to coupling plate	1520
D Length + bucket	2165	M Ground clearance	121
E Bucket angle when dumping	51°	N Rear Angle	14°
F Height underside of the bucket when dumping	1480	0 Turning radius	1606
G Length from front wheel to bucket when dumping	180	P Turning radius with bucket	2250
H Height bucket horizontally	1860	Q Width	760
I Bucket angle low	26°		

## TECHNICAL DATA SHERPA 100 ECO


Max. Dimensions (L mm x B mm x H mm, without bucket):


 Standard
 1490 x 760 x 1218

 Wide
 1490 x 1050 x 1218

Kerb weight 759 kg

#### Tipping loads (kg)\*:





- \* Including driver 60kg
- \*\* Consider a safety factor of 30%

### SHERPA 100 ECO

The SHERPA 100 ECO has brought about a true revolution in the world of construction and demolition work. By bundling the compact versatility of the SHERPA 100 and a powerful and durable electric motor, there is a SHERPA available that has incomparable benefits.

More information? Call us +31 412 61 33 44

Canadabaan 14 | 5388 RT Nistelrode | www.sherpaminiloaders.com





