

/ BREAKERS

BHB 205 · BHB 305 · BHB 455 · BHB 555

The Brokk hydraulic breaker is one of our most versatile attachments for your Brokk robot.

The BHB series offers the perfect combination of hard-hitting power and fast, efficient demolition. Our hydraulic breakers are expertly engineered to generate less noise and vibrations without compromising on design.

- Hard-hitting power
- Less noise and vibrations
- Quick tool change



	BHB 205 Brokk 170*, 200*		BHB 305 Brokk 200*, 300*		BHB 455 Brokk 300*, 900R		BHB 555 Brokk 500*, 520D	
Blows/min*	850 - 1800		600 - 1400		550 - 1250		650 - 1150	
Impact	406 J		610 J		855 J		1048 J	
Weight	205 kg	452 lbs	295 kg	650 lbs	410 kg	904 lbs	520 kg	1146 lbs
Pressure	150 bar	2176 psi	150 bar	2176 psi	150 bar	2176 psi	150 bar	2176 psi
Oil flow, min	35 l/min	9.2 gal/min	50 l/min	13.2 gal/min	55 l/min,	14.5 gal/min	65 l/min	17.2 gal/min
Oil flow, max	66 l/min	17.4 gal/min	88 l/min	23.2 gal/min	110 l/min	29.1 gal/min	115 l/min	30.4 gal/min
Floor**	2,9 m³/h	3.8 yd³/h	4,0 m³/h	5.2 yd³/h	5,1 m³/h	6.7 yd³/h	6,0 m³/h	7.8 yd³/h
Wall**	2,2 m³/h	2.9 yd³/h	3,0 m³/h	3.9 yd³/h	3,8 m³/h	4.9 yd³/h	4,5 m³/h	5.8 yd³/h
Ceiling**	1,8 m³/h	2.4 yd³/h	2,5 m³/h	3.3 yd³/h	3,3 m³/h	4.3 yd³/h	3,8 m³/h	4.9 yd³/h
Tool shank diameter	65 mm	2.6 in	80 mm	3.1 in	95 mm	3.7 in	100 mm	3.9 in

* Actual output, impact energy class (Joule/Nm)

** Estimated production rate in normal strength rebar reinforced concrete (approx.)