

/ BREAKERS

BHB 55 · BHB 105 · BHB 155 · BHB 175

The Brokk hydraulic breaker is one of our most versatile attachments for your Brokk robot.

The BHB series offers the perfect combination of hard-hitting power and fast, efficient demolition. Our hydraulic breakers are expertly engineered to generate less noise and vibrations without compromising on design.

- Hard-hitting power
- Less noise and vibrations
- Quick tool change



	BHB 55 Brokk 70*		BHB 105 Brokk 70*, 120D		BHB 155 Brokk 120D, 170*		BHB 175 Brokk 130*	
Blows/min*	750-1700		750-2300		850 - 1900		1000-2000	
Impact	101 J		159 J		254 J		276 J	
Weight	55 kg	121 lbs	100 kg	220 lbs	140 kg	309 lbs	160 kg	353 lbs
Pressure	150 bar	2176 psi	150 bar	2176 psi	150 bar	2176 psi	150 bar	2176 psi
Oil flow, min	12 l/min	3.2 gal/min	16 l/min,	4.2 gal/min	25 l/min	6.6 gal/min	30 l/min	7.9 gal/min
Oil flow, max	32 l/min	8.5 gal/min	35 l/min	9.2 gal/min	45 l/min	11.9 gal/min	50 l/min	13.2 gal/min
Floor**	0,8 m³/h	1 yd³/h			1,8 m³/h	2.3 yd³/h		
Wall**	0,6 m³/h	0.8 yd³/h			1,3 m³/h	1.7 yd³/h		
Ceiling**	0,5 m³/h	0.6 yd³/h			1,2 m³/h	1.5 yd³/h		
Tool shank diameter	40 mm	1.6 in	45 mm	1.8 in	50 mm	2 in	50 mm	2 in

* Actual output, impact energy class (Joule/Nm)

** Estimated production rate in normal strength rebar reinforced concrete (approx.)