



# The Masterpiece of Muscle, Reach and Size

There is a new weight class in town. The all new **BROKK 200** breaks new ground, packing the power of the Brokk 280 into a 2,1 ton compact package. This 27,5 kW Brokk SmartPower<sup>TM</sup> machine carries tools one weight class above its size and brings the power to match it. Paired with the BHB 305 breaker or the all-new Darda CC480 crusher, it is a brutal demolition machine. And of course it comes with the new signature Brokk SmartDesign<sup>TM</sup> and SmartRemote<sup>TM</sup> capabilities.

- Demolition power of a 3 ton Brokk in a 2 ton package
- Exceptionally small footprint for its power and reach
- ≥ 27,5 kW Brokk SmartPower<sup>™</sup> electrical system
- ➤ Brokk SmartDesign<sup>™</sup> and SmartRemote<sup>™</sup>
- Built and optimized for heavy highperformance tools





Hydraulic breaker in illustrations

Load and stability diagram available on request

# **Performance**

m/in

Slewing speed 10 sec/360° Transport speed, max. 2,1 km/h; 1.3 mph Climbing inclination, max.

## **Hydraulic system**

85 l; 22.5 US gal Hydraulic system capacity Variable load-sensing Pump type 18 MPa; 2 611 psi System pressure System pressure, increased to attachment, max. 25 MPa; 3 626 psi Pump flow 85 l/min; 22 US gal/min 50Hz 102 l/min; 27 US gal/min 60Hz

#### **Power system**

Power technology SmartPower Electric motor type ABB 27,5 kW Power\* Recommended fuse size\* 63 A Soft start/Direct start Starting device

## **Control system**

Control type SmartRemote, portable control Signal code Digital Transfer Professional radio/Cable Up to 300 m Range, radio

#### Weight

Machine weight\*\* 2 100 kg; 4 630 lbs 350 kg; 772 lbs Recommended max. attachment weight

#### **Noise level**

Sound power level LWA\*\*\* 87 dB(A)

\*Valid for 400V/50Hz and 440V/60Hz \*\*Excluding options and attachment

\*\*\*Measured according to directive 2000/14/EC, excl. attachment

### Arm System

BHB 305

Impact and heat protection for cylinder C2 and C3

# **Undercarriage**

Rubber caterpillar tracks Steel caterpillar tracks

## Heat resistance

Heat resistant hoses for hydraulic breaker Forced draft cooling of machine Forced draft cooling of breaker Steel pads for kiln demoliton or furnance

## Other options

Air flushing through breaker to protect from dust Water spray through breaker to bind dust Counterweight Extra hydraulic function Cable reel with 60 m cable Drainage hose CAN cable connection for tools

Lifting eyes (regular lifting points are standard)

