

# / CUT OFF SAW

Replace hand-held equipment with a Brokk Cut Off Saw.  
Saw blades for many different materials are available.

- Suitable for wall, ceiling, floor
- Depth can be set from control box - completely remote
- Automatic operation - one push activation



BCS 20

	<b>BCS 8</b> Brokk 70		<b>BCS 20*</b> Brokk 110, 120D		<b>BCS 25**</b> Brokk 170		<b>BCS 40*</b> Brokk 200	
<b>Cutting depth***</b>	150 mm	6 in	220 mm	9 in	270 mm	11 in	270 mm	11 in
<b>Saw disc diameter***</b>	400 mm	16 in	600 mm	24 in	800 mm	31 in	800 mm	31 in
<b>Weight</b>	70 kg	154 lbs	145 kg	320 lbs	215 kg	474 lbs	370 kg	816 lbs
<b>Motor</b>	7,4 cc	0.45 cu in	17 cc	1.04 cu in	25,4 cc	1.55 cu in	41,2 cc	2.51 cu in
<b>Oil flow, min</b>	25 l/min	6.6 gal/min	37 l/min	9.8 gal/min	37 l/min	9.8 gal/min	60 l/min	15.9 gal/min
<b>Working pressure, max</b>	180 bar	2611 psi	180 bar	2611 psi	180 bar	2611 psi	180 bar	2611 psi
<b>Temperature, max</b>	55 °C	130 °F	55 °C	130 °F	55 °C	130 °F	55 °C	130 °F

	<b>BCS 45*</b> Brokk 300		<b>BCS 65*</b> Brokk 500, 520D		<b>BCS 90*</b> Brokk 900	
<b>Cutting depth*</b>	270 mm	11 in	270 mm	11 in	370 mm	15 in
<b>Saw disc diameter**</b>	800 mm	31 in	800 mm	31 in	1000 mm	47 in
<b>Weight</b>	375 kg	827 lbs	390 kg	860 lbs	515 kg	1135 lbs
<b>Motor</b>	47,1 cc	2.87 cu in	63,5 cc	3.88 cu in	90,7 cc	5.53 cu in
<b>Oil flow, min</b>	68 l/min	18 gal/min	93 l/min	24.6 gal/min	89 l/min	23.5 gal/min
<b>Working pressure, max</b>	170 bar	2466 psi	185 bar	2683 psi	185 bar	2683 psi
<b>Temperature, max</b>	55 °C	130 °F	55 °C	130 °F	55 °C	130 °F

Requires one extra hydraulic function

\* Requires drainage hose and CAN cable

\*\* Requires drainage hose

\*\*\* Optional saw disc type and sizes are available upon request