

/ CUT OFF SAW

Replace hand-held equipment with a Brokk Cut Off Saw.
Saw blades for many different materials are available.

- Suitable for wall, ceiling, floor
- Depth can be set from control box – completely remote
- Automatic operation – one push activation



BCS 10

	BCS 8 Brokk 70	BCS 10 Brokk 110, 120D	BCS 25*** Brokk 170	BCS 40*** Brokk 200
Cutting depth*	170 mm/7 in	170 mm/7 in	270 mm/11 in	470 mm/19 in
Saw disc diameter**	400 mm/16 in	400 mm/16 in	800 mm/31 in	1200 mm/47 in
Weight	70 kg/154 lbs	85 kg/187 lbs	215 kg/474 lbs	370 kg/816 lbs
Motor	7,4 cc/0.45 cu in	9,5 cc/0.58 cu in	25,4 cc/1.55 cu in	41,2 cc/2.51 cu in
Oil flow, min	25 l/min, 6.6 gal/min	32 l/min, 8.5 gal/min	37 l/min, 9.8 gal/min	60 l/min, 15.9 gal/min
Working pressure, max	180 bar/2611 psi	180 bar/2611 psi	180 bar/2611 psi	180 bar/2611 psi
Temperature, max	55 °C/130 °F	55 °C/130 °F	55 °C/130 °F	55 °C/130 °F

	BCS 45*** Brokk 300	BCS 65*** Brokk 500, 520D	BCS 90*** Brokk 900
Cutting depth*	470 mm/19 in	470 mm/19 in	470 mm/19 in
Saw disc diameter**	1200 mm/47 in	1200 mm/47 in	1200 mm/47 in
Weight	375 kg/827 lbs	390 kg/860 lbs	515 kg/1135 lbs
Motor	47,1 cc/2.87 cu in	63,5 cc/3.88 cu in	90,7 cc/5.53 cu in
Oil flow, min	68 l/min, 18 gal/min	93 l/min, 24.6 gal/min	89 l/min, 23.5 gal/min
Working pressure, max	170 bar/2466 psi	185 bar/2683 psi	185 bar/2683 psi
Temperature, max	55 °C/130 °F	55 °C/130 °F	55 °C/130 °F

Requires one extra hydraulic function

* With new saw disk

** Different saw disks available depending on material

*** Requires drainage hose and CAN cable