

Brokk planers remove concrete, paint, asbestos, or other layers in a controlled manner up to a certain depth and can also be equipped with a suction hose.

- > Suitable for wall, ceiling, floor
- > Depth can be set from control box completely remote
- > Automatic operation one push activation



	BCP 215* Brokk 110, 120D	BCP 250 Brokk 200	BCP 350 Brokk 300, 500, 520D
Width	640 mm/25 in	640 mm/25 in	720 mm/28 in
Length	1840 mm/72 in	2066 mm/81 in	2070 mm/81 in
Stroke length	1300 mm/51.2 in	1530 mm/60.2 in	1400 mm/55.1 in
Cutting width	265 mm/10.4 in	265 mm/10.4 in	335 mm/13.2 in
Cutting depth, per stroke**	0-5 mm/0.2 in	0-5 mm/0.2 in	0-5 mm/0.2 in
Cutting depth, max**	12 mm/0.5 in	12 mm/0.5 in	12 mm/0.5 in
Weight	230 kg/507 lbs	345 kg/761 lbs	600 kg/1323 lbs
Connection pressure, min	165 bar/2393 psi	165 bar/2393 psi	165 bar/2393 psi
Connection pressure, max	175 bar/2538 psi	175 bar/2538 psi	175 bar/2538 psi
Oil flow	45 l/min, 11.9 gal/min	45 l/min, 11.9 gal/min	65 l/min, 17.2 gal/min

Available with cover and suction.

 $Requires\ extra\ hydraulic\ function, drainage\ hose, CAN\ cable, counterweight\ in\ some\ occations.\ Requires\ load\ holding.\ On\ request.$

^{*}Extra pressure level needed

^{**}Data depending on concrete quality