

/ BREAKERS

BHB 305 · BHB 455 · BHB 555 · BHB 705

The Brokk hydraulic breaker is one of our most versatile attachments for your Brokk robot. The BHB series offers the perfect combination of hard-hitting power and fast, efficient demolition. Our hydraulic breakers are expertly engineered to generate less noise and vibrations without compromising on design.

- Hard-hitting power
- Less noise and vibrations
- Quick tool change



	BHB 305 Brokk 200, 300		BHB 455 Brokk 300, 900R		BHB 555 Brokk 500, 520D		BHB 705 Brokk 500, 520D	
Blows/min*	600 - 1400		550 - 1250		650 - 1150		600 - 1050	
Impact	610 J		855 J		1048 J		1472 J	
Weight	295 kg	650 lbs	410 kg	904 lbs	520 kg	1146 lbs	685 kg	452 lbs
Pressure	150 bar	2176 psi	150 bar	2176 psi	150 bar	2176 psi	170 bar	2466 psi
Oil flow, min	50 l/min	13.2 gal/min	55 l/min,	14.5 gal/min	65 l/min	17.2 gal/min	80 l/min	21.1 gal/min
Oil flow, max	88 l/min	23.2 gal/min	110 l/min	29.1 gal/min	115 l/min	30.4 gal/min	120 l/min	31.7 gal/min
Floor**	4,0 m ³ /h	5.2 yd ³ /h	5,1 m ³ /h	6.7 yd ³ /h	6,0 m ³ /h	7.8 yd ³ /h		
Wall**	3,0 m ³ /h	3.9 yd ³ /h	3,8 m ³ /h	4.9 yd ³ /h	4,5 m ³ /h	5.8 yd ³ /h		
Ceiling**	2,5 m ³ /h	3.3 yd ³ /h	3,3 m ³ /h	4.3 yd ³ /h	3,8 m ³ /h	4.9 yd ³ /h		
Tool shank diameter	80 mm	3.1 in	95 mm	3.7 in	100 mm	3.9 in	105 mm	4.1 in

* Actual output, impact energy class (Joule/Nm)

** Estimated production rate in normal strength rebar reinforced concrete (approx.)