

# BREAKERS

BHB 55 · BHB 105 · BHB 155 · BHB 205

The Brokk hydraulic breaker is one of our most versatile attachments for your Brokk robot. The BHB series offers the perfect combination of hard-hitting power and fast, efficient demolition. Our hydraulic breakers are expertly engineered to generate less noise and vibrations without compromising on design.

- Hard-hitting power
- Less noise and vibrations
- Quick tool change



	<b>BHB 55</b> Brokk 70		<b>BHB 105</b> Brokk 70, 110, 120D		<b>BHB 155</b> Brokk 110, 120D, 170		<b>BHB 205</b> Brokk 170, 200	
<b>Blows/min*</b>	750-1700		750-2300		850 - 1900		850 - 1800	
<b>Impact</b>	101 J		159 J		254 J		406 J	
<b>Weight</b>	55 kg	121 lbs	100 kg	220 lbs	140 kg	309 lbs	205 kg	452 lbs
<b>Pressure</b>	150 bar	2176 psi	150 bar	2176 psi	150 bar	2176 psi	150 bar	2176 psi
<b>Oil flow, min</b>	12 l/min	3.2 gal/min	16 l/min,	4.2 gal/min	25 l/min	6.6 gal/min	35 l/min	9.2 gal/min
<b>Oil flow, max</b>	32 l/min	8.5 gal/min	35 l/min	9.2 gal/min	45 l/min	11.9 gal/min	66 l/min	17.4 gal/min
<b>Floor**</b>	0,8 m <sup>3</sup> /h	1 yd <sup>3</sup> /h			1,8 m <sup>3</sup> /h	2.3 yd <sup>3</sup> /h	2,9 m <sup>3</sup> /h	3.8 yd <sup>3</sup> /h
<b>Wall**</b>	0,6 m <sup>3</sup> /h	0.8 yd <sup>3</sup> /h			1,3 m <sup>3</sup> /h	1.7 yd <sup>3</sup> /h	2,2 m <sup>3</sup> /h	2.9 yd <sup>3</sup> /h
<b>Ceiling**</b>	0,5 m <sup>3</sup> /h	0.6 yd <sup>3</sup> /h			1,2 m <sup>3</sup> /h	1.5 yd <sup>3</sup> /h	1,8 m <sup>3</sup> /h	2.4 yd <sup>3</sup> /h
<b>Tool shank diameter</b>	40 mm	1.6 in	45 mm	1.8 in	50 mm	2 in	65 mm	2.6 in

\* Actual output, impact energy class (Joule/Nm)

\*\* Estimated production rate in normal strength rebar reinforced concrete (approx.)